RG5 BRONZE VALVES

Flanged Gate Valve with Indicator, RG5 Bronze, PN16

DIN 3352-11 PN16


Bronze Flanged Gate Valves with Position Indicator, DN 25–100. Tested with water: body 20, disc 20 bar. For transformer oil and water.



MATERIALS

	DN25–DN65	DN80–DN100
Body	RG-5 Bronze	RG-5 Bronze
Bonnet	MS-58 Brass	RG-5 Bronze
Wedge	MS-58 Brass	RG-5 Bronze
Seat Rings	RG-5 Bronze	RG-5 Bronze
Bonnet Gasket	Frenzelit	Frenzelit
Stem	MS-58 Brass	MS-58 Brass
Packing	NBR	NBR
Indicator	MS-58 Brass	MS-58 Brass
Handwheel	MS-58 Brass	MS-58 Brass
Handwheel Nut & Washer	Stainless Steel	Stainless Steel

DRAWING



PRODUCT DESCRIPTION

O.S.K. ÇAVUŞYAN Bronze Flanged Gate Valves with Position Indicator; Body is made of Rg-5 bronze • Bonnet and the wedge are made of MS-58 brass • Non-rising stem is made of MS-58 brass • Nominal pressure is PN 16 for DN 25 to DN 65 • DN 80 and DN 100 Flanged Gate Valves' body, bonnet and wedge are made of RG5 bronze • Other components are MS-58 brass.

TECHNICAL DATA

According to DIN 3352-11: 16 bar nominal pressure (PN 16) at temperatures up to 120 °C

TESTS

Test Liquid	Water at Room Temp
Body Test	20 Bar
Disc Test	20 Bar
Test Standard No	TS 457

USE

Transformer oil (max. 10 bar, 120 °C)
Water (non-potable)

DIMENSIONS

DN	d1	L	h	d4	s	k	No.	d3	Kg
25	115	80	150	60	10	85	4	14	2,8
40	150	100	200	80	10,5	110		18	5
50	165	110	240	100	11,5	125			7,3
65	185	130	280	120	14	145			10,2
80	200	150	300	140		160	8		13,3
100	220	185	442	180	15	180			20

Note: Dimensions are given in millimetres.

O.S.K. ÇAVUŞYAN Vana Sanayi ve Ticaret Ltd. Şti.
Bakır Sok. No 7, Perşembe Pazarı, Karaköy, 34420 Beyoğlu / Istanbul, Turkey
Tel +90 212 237 65 37 · Fax +90 212 250 63 45 · oskvana@gmail.com · oskvana.com

This product online
https://oskvana.com/products/din-transformer-valves/flanged-gate-valves-with-position-indication-rg5-bronze-pn16/
Date: 14 Nov 2026